

X1 5W30

OEM GROUP A
ESTER HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Ester based synthetic high performance engine oil that provides optimum protection and extended engine life and reliability. It exceeds the performance requirements of virtually all engine manufacturers. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics.

PROPERTIES

- Reduced fuel consumption and CO₂ emissions
- Helps to deliver important boost in engine power
- High and very stable viscosity index
- Fast cold start
- Delivers superior thermal stability, ensuring minimal engine deposits for cleaner internals
- Ensures engine protection from the first moment of ignition, minimizing wear and damage
- Protects Diesel Particle Filters



APPLICATION

Suitable for both turbocharged and normally aspirated petrol & diesel engines.
Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5040
Viscosity 40 °C, mm ² /s	65,90
Viscosity 100 °C, mm ² /s	11,60
Viscosity Index	173
Flash Point COC, °C	232
Pour Point, °C	-45
Total Base Number, mgKOH/g	6,5
Sulphate Ash, %	0,67

SPECIFICATIONS

ACEA C3
VW 504.00 – 507.00
MB 229.51
Porsche C30
BMW LL-04 (pending)

PACKAGING

1L can (12 x 1L carton)
5L can (4 x 5L carton)
60 L drum
208 L drum