

X2 10W40

HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Universal, fuel economy, specially composed hybrid synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

PROPERTIES

- Reduces oil consumption.
- Very stable viscosity index.
- High resistance against shearing.
- Increases oil pressure.
- Strong resistance and protection against wear.
- Powerful detergency prevents deposits in the engine.
- Safe lubrication film.
- Very good detergency.

APPLICATION

Recommended for use in all petrol and diesel engines, with or without turbo charging, in passenger cars and delivery vans where the according specifications are required.

Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.



TYPICALS

Density at 15 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	5470
Viscosity 40 °C, mm ² /s	91,60
Viscosity 100 °C, mm ² /s	13,80
Viscosity Index	154
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,26

SPECIFICATIONS

ACEA A3/B4-12
API SN/CF

Meets the requirements of
MB 229.1

PACKAGING

1 L can (12 x 1L box)
5 L can (4 x 5L box)
60 L drum
208 L drum