

XA-TRAN 8G

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives.

PROPERTIES

- Important contribution fuel economy.
- Excellent lubrication.
- very good resistance against oxidation and a very high thermal stability
- excellent resistance against foaming
- excellent protection against wear.
- very high and stable viscosity index
- excellent and very stable friction characteristics that enable longer oil-replacement intervals



APPLICATION

This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

TYPICALS

Density at 15 °C, kg/l	0,845
Viscosity at 40 °C, mm ² /s	25,80
Viscosity at 100 °C, mm ² /s	6,00
Viscosity index	190
Flash point COC, °C	198
Poor point, °C	-45

SPECIFICATIONS

VAG G-060-162
BMW 8322 2152426/2289720(ATF3+)
Jaguar 02JDE 26444
Land Rover LR023288
Chrysler 68157995AA
Fiat 9.55550-AV5

PACKAGING

1L can (12 x 1L carton)
4 L can (4 x 4L carton)
60 L drum
208 L drum